

## Wedge Anchor FWA

Recommended loads of a single anchor<sup>1)</sup> in normal concrete of strength class 3000 Psi.

Type	Material / surface <sup>3)</sup>	Effective anchorage depth $h_{ef} \geq$ [in]	Minimum member thickness $h_{min}$ [in]	Drill hole diameter $d_0$ [in]	Drill hole diameter in fixture <sup>2)</sup> $d_f$ [in]	Installation torque $T_{inst}$ [lbf-ft]	Non-cracked concrete			
							Recommended tension ( $N_{rec}$ ), shear loads ( $V_{rec}$ ), minimum spacing ( $s_{min}$ ) and edge distances ( $c_{min}$ )			
							$N_{rec}^{3)}$ [lb]	$V_{rec}^{3)}$ [lb]	$s_{min}^{3)}$ [in]	$c_{min}^{3)}$ [in]
FWA 1/4	gvz	1	4	1/4	3/8	3	202	-	3	1 1/2
	gvz	1 1/8	4	1/4	3/8	3	540	315	3 1/2	1 3/4
FWA 5/16	gvz	1 1/4	4	5/16	7/16	7	719	427	3 3/4	1 7/8
FWA 3/8	gvz	1 1/8	4	3/8	1/2	19	472	-	3 1/2	1 3/4
	gvz	1 5/16	4	3/8	1/2	19	944	562	4	2
FWA 1/2	gvz	1 3/8	4	1/2	5/8	30	764	-	4 1/8	2 1/8
	gvz	1 7/8	4	1/2	5/8	30	1461	854	5 3/4	2 7/8
FWA 5/8	gvz	2	4	5/8	7/8	74	1124	-	6	3 1/8
	gvz	2 3/8	4 3/4	5/8	7/8	74	2158	1281	7 1/8	3 5/8
FWA 3/4	gvz	2 1/2	5	3/4	1	148	2428	-	7 5/8	3 7/8
	gvz	2 3/4	5 1/2	3/4	1	148	3147	1866	8 1/4	4 1/8
FWA 1"	gvz	3 3/4	7 1/2	1	1 1/4	192	4406	-	11 1/4	5 5/8
	gvz	3 7/8	7 3/4	1	1 1/4	192	4676	-	11 5/8	5 7/8

<sup>1)</sup> The partial safety factors for material resistance as well as a partial safety factor for load actions of  $\gamma_t = 1.4$  are considered. As a single anchor counts e.g. an anchor with a spacing  $s \geq 3 \times h_{ef}$  and an edge distance  $c \geq 1.5 \times h_{ef}$ .

<sup>2)</sup> For push-through installation.

<sup>3)</sup> As recommended loades are given in the table, combinations of tensile and shear loads, bending moments and reduced edge and axial spacings (anchor groups) can not be carried out.